

FS 964 ACT

Fibre discs for Steel, Stainless steel



Applications

Steel



Stainless steel



Properties

Bonding agent Resin

Grain Ceramic aluminium oxide

Coating Close

Advantages: Premium product with excellent performance for working on steel - Micro-crystalline self-sharpening effect - High aggressiveness thanks to self-sharpening, aggressive ceramic grains throughout the service life - Outstanding grit adhesion - Advanced coating technology (ACT) for extraordinary grain adhesion and extended service life

Available grits

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------

Diameter in mm	Bore in mm	Grit	Vmax in m/s	Max. RPM in rpm	Cat.number
115	22	24	80	13300	330478
115	22	60	80	13300	330479
115	22	50	80	13300	330480
115	22	80	80	13300	330481
115	22	40	80	13300	330482
115	22	36	80	13300	330498
125	22	24	80	12200	330484
125	22	36	80	12200	330485
125	22	40	80	12200	330486
125	22	60	80	12200	330487
125	22	50	80	12200	330488
125	22	80	80	12200	330490
125	22	120	80	12200	330491

180	22	24	80	8500	330489
180	22	36	80	8500	330492
180	22	40	80	8500	330493
180	22	50	80	8500	330494
180	22	60	80	8500	330495
180	22	80	80	8500	330496
180	22	120	80	8500	330497