

FS 964 ACT

Fibre discs for Steel, Stainless steel



Applications

Steel
Stainless steel



Properties

Bonding agent Resin
Grain Ceramic aluminium oxide
Coating Close

Advantages: Premium product with excellent performance for working on steel - Micro-crystalline self-sharpening effect - High aggressiveness thanks to self-sharpening, aggressive ceramic grains throughout the service life - Outstanding grit adhesion - Advanced coating technology (ACT) for extraordinary grain adhesion and extended service life

Available grits

16 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000

Diameter in mm	Bore in mm	Grit	Vmax in m/s	Max. RPM in rpm	Cat. number
115.0	22	24	80	13300.0	330478
115.0	22	60	80	13300.0	330479
115.0	22	50	80	13300.0	330480
115.0	22	80	80	13300.0	330481
115.0	22	40	80	13300.0	330482
125.0	22	24	80	12200.0	330484
125.0	22	36	80	12200.0	330485
125.0	22	40	80	12200.0	330486
125.0	22	60	80	12200.0	330487
125.0	22	50	80	12200.0	330488
180.0	22	24	80	8500.0	330489
125.0	22	80	80	12200.0	330490
125.0	22	120	80	12200.0	330491

180.0	22	36	80	8500.0	330492
180.0	22	40	80	8500.0	330493
180.0	22	50	80	8500.0	330494
180.0	22	60	80	8500.0	330495
180.0	22	80	80	8500.0	330496
180.0	22	120	80	8500.0	330497
115.0	22	36	80	13300.0	330498