

Abrasive film, self fastening

FP 77 K T-ACT



Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Semi-open
Backing	Film

Product benefit

New high-performance product with optimized clogging behaviour
 - Increased service life due to the new coating, which prevents the adhesion of paint and dust particles
 - For fine sanding in the fine grit range 240 - 2000, a highly flexible and completely flat film backing is used for highest surface quality

Application

Paint/Varnish/Filler	●
Primer	●
Filler	●
Gel coats	●
Composite materials	●
Plastic	●

Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------

Width x Length in mm	grain	Hole pattern	type of coat.abras.	Packing unit/pcs.	Cat. number
80 x 133	240	GL 18	FP 77 K	100	353120
80 x 133	320	GL 18	FP 77 K	100	353119
80 x 133	400	GL 18	FP 77 K	100	353118

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de

