
Abrasive fibre disc

CS 565





Properties

Bonding agent	Resin
Grain	Zirconia alumina
Coating	Close

Application

Stainless steel	●
Steel	●
Metals	●

Product benefit

Self-sharpening effect - High aggressiveness on steel and stainless steel - Ideal for rough grinding work - Excellent price-performance ratio|Self-sharpening effect - High aggressiveness on steel and stainless steel - Ideal for rough grinding work - Excellent price-performance ratio - Special large package reduces storage costs

Applications

- Steel construction
- Stainless steel processing industry
- Metal construction

Available grits:

16 | 24 | 30 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 | 3000

Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number
100 x 16	⊙ 10	80	80 m/s	15300 rpm	CS 565	round hole	25	188678
100 x 16	⊙ 10	36	80 m/s	15300 rpm	CS 565	round hole	25	23680
100 x 16	⊙ 10	60	80 m/s	15300 rpm	CS 565	round hole	25	84604
115 x 22	⊛ 30	100	80 m/s	13300 rpm	CS 565	star shaped hole	25	204609

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number
115 x 22	⊛ 30	40	80 m/s	13300 rpm	CS 565	star shaped hole	25	242801
115 x 22 X-LOCK	⊛ 50	36	80 m/s	13300 rpm	CS 565	X-LOCK	25	351140
115 x 22 X-LOCK	⊛ 50	24	80 m/s	13300 rpm	CS 565	X-LOCK	25	351141
115 x 22 X-LOCK	⊛ 50	40	80 m/s	13300 rpm	CS 565	X-LOCK	25	351154
115 x 22 X-LOCK	⊛ 50	80	80 m/s	13300 rpm	CS 565	X-LOCK	25	351159
115 x 22 X-LOCK	⊛ 50	60	80 m/s	13300 rpm	CS 565	X-LOCK	25	351160
115 x 22	⊙ 10	36	80 m/s	13300 rpm	CS 565	round hole	25	65698
115 x 22	⊙ 10	60	80 m/s	13300 rpm	CS 565	round hole	25	65700
115 x 22	⊙ 10	80	80 m/s	13300 rpm	CS 565	round hole	25	65701
115 x 22	⊛ 30	36	80 m/s	13300 rpm	CS 565	star shaped hole	25	6686
115 x 22	⊛ 30	60	80 m/s	13300 rpm	CS 565	star shaped hole	25	6687
115 x 22	⊛ 30	80	80 m/s	13300 rpm	CS 565	star shaped hole	25	6688
115 x 22	⊛ 30	50	80 m/s	13300 rpm	CS 565	star shaped hole	25	92066
115 x 22	⊙ 10	24	80 m/s	13300 rpm	CS 565	round hole	25	93409
115 x 22	⊛ 30	24	80 m/s	13300 rpm	CS 565	star shaped hole	25	95335
125 x 22	⊛ 30	100	80 m/s	12200 rpm	CS 565	star shaped hole	25	204611
125 x 22	⊙ 10	80	80 m/s	12200 rpm	CS 565	round hole	25	23001
125 x 22	⊛ 30	80	80 m/s	12200 rpm	CS 565	star shaped hole	25	23005
125 x 22	⊙ 10	40	80 m/s	12200 rpm	CS 565	round hole	25	242802
125 x 22	⊛ 30	40	80 m/s	12200 rpm	CS 565	star shaped hole	25	242803
125 x 22 X-LOCK	⊛ 50	80	80 m/s	12200 rpm	CS 565	X-LOCK	25	351155
125 x 22 X-LOCK	⊛ 50	60	80 m/s	12200 rpm	CS 565	X-LOCK	25	351156
125 x 22 X-LOCK	⊛ 50	40	80 m/s	12200 rpm	CS 565	X-LOCK	25	351157
125 x 22 X-LOCK	⊛ 50	24	80 m/s	12200 rpm	CS 565	X-LOCK	25	351158
125 x 22 X-LOCK	⊛ 50	36	80 m/s	12200 rpm	CS 565	X-LOCK	25	351161
125 x 22	⊙ 10	36	80 m/s	12200 rpm	CS 565	round hole	25	65681
125 x 22	⊙ 10	60	80 m/s	12200 rpm	CS 565	round hole	25	65707
125 x 22	⊛ 30	36	80 m/s	12200 rpm	CS 565	star shaped hole	25	6620

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number
125 x 22	⊛ 30	60	80 m/s	12200 rpm	CS 565	star shaped hole	25	6721
125 x 22	⊛ 30	50	80 m/s	12200 rpm	CS 565	star shaped hole	25	93054
125 x 22	⊛ 30	24	80 m/s	12200 rpm	CS 565	star shaped hole	25	97643
180 x 22	⊛ 30	40	80 m/s	8500 rpm	CS 565	star shaped hole	25	242807
180 x 22	⊙ 10	36	80 m/s	8500 rpm	CS 565	round hole	25	65702
180 x 22	⊛ 30	36	80 m/s	8500 rpm	CS 565	star shaped hole	25	65703
180 x 22	⊙ 10	60	80 m/s	8500 rpm	CS 565	round hole	25	65705
180 x 22	⊙ 10	80	80 m/s	8500 rpm	CS 565	round hole	25	65706
180 x 22	⊛ 30	60	80 m/s	8500 rpm	CS 565	star shaped hole	25	6690
180 x 22	⊛ 30	80	80 m/s	8500 rpm	CS 565	star shaped hole	25	6691
180 x 22	⊛ 30	50	80 m/s	8500 rpm	CS 565	star shaped hole	25	93045
180 x 22	⊛ 30	24	80 m/s	8500 rpm	CS 565	star shaped hole	25	95993

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de