

Cutting-off wheel

A 24 EXTRA



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■□□□
Aggression	■■■■□□□
Service life	■■■■□□□

Product benefit

Proven a million times over - Standard wheel with outstanding price-performance ratio - For universal use in metalworking - Fast cutting off of solid material

Materials

Metals ●

Applications










- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 2,5 x 16		80 m/s	15300 rpm	25	188998
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	242137
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	188461
115 x 2,5 x 22,23 X-LOCK		80 m/s	13300 rpm	25	351255
115 x 3,2 x 22,23		80 m/s	13300 rpm	25	209014
125 x 2,5 x 22,23		80 m/s	12200 rpm	25	242138
125 x 2,5 x 22,23		80 m/s	12200 rpm	25	188463
125 x 2,5 x 22,23 X-LOCK		80 m/s	12200 rpm	25	351254

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de



Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
125 x 3,2 x 22,23		80 m/s	12200 rpm	25	209016
150 x 2,5 x 22,23		80 m/s	10200 rpm	25	235375
150 x 2,5 x 22,23		80 m/s	10200 rpm	25	235374
180 x 2 x 22,23		80 m/s	8500 rpm	25	286455
180 x 3 x 22,23		80 m/s	8500 rpm	25	13490
180 x 3 x 22,23		80 m/s	8500 rpm	25	189000
230 x 2 x 22,23		80 m/s	6600 rpm	25	286456
230 x 3 x 22,23		80 m/s	6600 rpm	25	13492
230 x 3 x 22,23		80 m/s	6600 rpm	25	189002

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

