

Cutting-off wheel

A 46 TZ SPECIAL



Fe-S-Cl
<0,1%



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■■□
Aggression	■■■■■■■□
Service life	■■■■■■■□

Product benefit

Free of iron, sulphur and chlorine - Universal use on steel and stainless steel - First choice for professional applications and fast cutting of demanding materials

Materials

Stainless steel	●
Steel	●

Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 1,6 x 16		80 m/s	15300 rpm	25	194071
115 x 1,6 x 22,23		80 m/s	13300 rpm	25	187170
115 x 1,6 x 22,23		80 m/s	13300 rpm	25	235378
115 x 1,6 x 22,23 X-LOCK		80 m/s	13300 rpm	25	351257
125 x 1,6 x 22,23		80 m/s	12200 rpm	25	187171
125 x 1,6 x 22,23		80 m/s	12200 rpm	25	235379







Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de



Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
125 x 1,6 x 22,23 X-LOCK		80 m/s	12200 rpm	25	351256
150 x 1,6 x 22,23		80 m/s	10200 rpm	25	241472
180 x 1,6 x 22,23		80 m/s	8500 rpm	25	221161
180 x 1,6 x 22,23		80 m/s	8500 rpm	25	312257
230 x 1,9 x 22,23		80 m/s	6600 rpm	25	224084
230 x 1,9 x 22,23		80 m/s	6600 rpm	25	265044

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

