

# Cutting-off wheel

# A 630 N SUPRA



## Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□
Aggression	■■■■■□
Service life	■■■■■□

## Product benefit

Aggressive model with an outstanding service life - An exceptional choice for the cutting of solid material - Bond optimized for universal use - Low thermal load - Minimum burr formation

## Materials

Steel	●
Stainless steel	○
Aluminium	○
Castings	○

## Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Locksmith's shop
- ▶ Steel construction
- ▶ Road building
- ▶ Construction above and below ground

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
300 x 2,5 x 25,4	— —	80 m/s	5100 rpm	10	353325
356 x 2,5 x 25,4	— —	80 m/s	4400 rpm	10	353324
406 x 3,2 x 25,4	— —	80 m/s	3800 rpm	10	353328

**Klingspor Schleifsysteme GmbH und Co. KG**

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

