

Cutting-off wheel

A 980 TZ SPECIAL



Fe-S-Cl
<0,1%



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□
Aggression	■■■■■□□
Service life	■■■■■□

Product benefit

Free of iron, sulphur and chlorine - Very short cutting times - Particularly precise and clean cuts due to the low thickness - Low thermal load - Minimal burr formation, minimizing finish-machining - 10 pieces in a tin with viewing window for easy removal

Materials

Stainless steel	●
Steel	●
NF metals	●

Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 0,8 x 22,23		80 m/s	13300 rpm	50	362548
125 x 0,8 x 22,23		80 m/s	12200 rpm	50	362549

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

