

Non-woven convolute wheels

NCO 700 DB



Properties

Bonding agent	Resin
Grain	SiC

Product benefit

Open structure, no clogging - Excellent satin finish with very low surface roughness - Good service life, consistent, reproducible finish - Removal of medium (7SF) to heavy burrs (9SF) without secondary burr formation - Cost-effective version with excellent price/performance ratio for applications with lower rotational speeds

Materials

Stainless steel	●
Titanium/Alloy	●
Steel	●
High alloy steel	●
NF metals	●
Aluminium	●
Plastic	◐

Applications

- ▶ Medical engineering
- ▶ Apparatus and container manufacturing
- ▶ Engine construction
- ▶ Foundries
- ▶ Fittings manufacturers

Diameter x Width x Bore in mm	Density	Grade	Colour	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
152,4 x 25,4 x 25,4	7 SF	fine	grey	47 m/s	6000 rpm	2	366498
152,4 x 25,4 x 25,4	8 SF	fine	grey	47 m/s	6000 rpm	2	366499
152,4 x 25,4 x 25,4	9 SF	fine	grey	47 m/s	6000 rpm	2	366500
203,2 x 51 x 76,2	7 SF	fine	grey	36 m/s	3450 rpm	1	367522

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de



Diameter x Width x Bore in mm	Density	Grade	Colour	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
203,2 x 51 x 76,2	8 SF	fine	grey	36 m/s	3450 rpm	1	367523
203,2 x 51 x 76,2	9 SF	fine	grey	36 m/s	3450 rpm	1	367524

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

