

# Combi non-woven web drum

## NCW 600 S



### Properties

Bonding agent	Resin
Grain	Aluminium oxide

### Product benefit

High removal rate and fine surface scratch pattern due to combination of non-woven and abrasive cloth flaps - Long service life

### Application

Stainless steel	●
Metals	●
Plastic	○

Diameter x Width x Bore in mm	grain	Form	Grade	Colour	Grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 50 x 19	80		coarse	maroon	aluminium oxide	19 m/s	3700 rpm	3	259896
100 x 50 x 19	100		medium	maroon	aluminium oxide	19 m/s	3700 rpm	3	259897
100 x 50 x 19	150		medium	maroon	aluminium oxide	19 m/s	3700 rpm	3	259898
100 x 50 x 19	180		very fine	maroon	aluminium oxide	19 m/s	3700 rpm	3	259899
100 x 100 x 19	80		coarse	maroon	aluminium oxide	19 m/s	3700 rpm	1	258905
100 x 100 x 19	100		medium	maroon	aluminium oxide	19 m/s	3700 rpm	1	258906

**Klingspor Schleifsysteme GmbH und Co. KG**  
 Hüttenstraße 36 - 35708 Haiger - Germany  
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186  
 sales@klingspor.de - www.klingspor.de



Diameter x Width x Bore in mm	grain	Form	Grade	Colour	Grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 100 x 19	150		medium	maroon	aluminium oxide	19 m/s	3700 rpm	1	258907
100 x 100 x 19	180		very fine	maroon	aluminium oxide	19 m/s	3700 rpm	1	258908
110 x 100 x 19	80		coarse	maroon	aluminium oxide	19 m/s	3300 rpm	1	320246
110 x 100 x 19	100		medium	maroon	aluminium oxide	19 m/s	3300 rpm	1	320247
110 x 100 x 19	150		medium	maroon	aluminium oxide	19 m/s	3300 rpm	1	320248

**Klingspor Schleifsysteme GmbH und Co. KG**

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

