

# Combi non-woven web mop

## NCW 600



### Properties

Bonding agent	Resin
Grain	Aluminium oxide

### Product benefit

Combination of non-woven and abrasive cloth flaps for a fine surface scratch pattern - Optimal wear properties - High removal rate - Long service life

### Materials


Stainless steel	●
Metals	●
Plastic	●

Diameter x Width x Bore in mm	grain	Form	Grade	Colour	Grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
165 x 50 x 43,1	80	☒	coarse	maroon	aluminium oxide	32 m/s	3700 rpm	3	258909
165 x 50 x 43,1	100	☒	medium	maroon	aluminium oxide	32 m/s	3700 rpm	3	258910
165 x 50 x 43,1	150	☒	medium	maroon	aluminium oxide	32 m/s	3700 rpm	3	258911
165 x 50 x 43,1	180	☒	very fine	maroon	aluminium oxide	32 m/s	3700 rpm	3	258912
200 x 50 x 68,2	80	☒	coarse	maroon	aluminium oxide	32 m/s	3050 rpm	2	258913
200 x 50 x 68,2	100	☒	medium	maroon	aluminium oxide	32 m/s	3050 rpm	2	258914

### Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany  
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186  
 sales@klingspor.de - www.klingspor.de



Diameter x Width x Bore in mm	grain	Form	Grade	Colour	Grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
200 x 50 x 68,2	150		medium	maroon	aluminium oxide	32 m/s	3050 rpm	2	258915

**Klingspor Schleifsysteme GmbH und Co. KG**

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

