# Abrasive screen, self-fastening, waterproof

# AN 400

## Properties

| | |
|---|---|
| Bonding agent | Resin |
| Grain | Aluminium oxide |
| Backing | Polyester screen |

## Materials

| | |
|---|---|
| Paint/Varnish/Filler | ● |
| Gel coats | ● |
| Plaster | ● |
| Plasterboard walls | ● |
| Composite materials | ● |
| Wood | ● |
| Wood-based materials | ● |

## Product benefit

Effective and full-surface dust extraction thanks to open grid structure - Dust-free grinding extends the service life of the abrasive - At the same time, improved health and safety thanks to reduced dust formation at the work station - Independent of existing extraction hole patterns - Waterproof

**Available grits:**

16 20 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

| Width x Length in mm | grain | Packing unit/pcs. | Cat. number |
|---|---|---|---|
| 115 x 10000 | 80 | 1 | 348458 |
| 115 x 10000 | 100 | 1 | 353063 |
| 115 x 10000 | 120 | 1 | 348418 |
| 115 x 10000 | 180 | 1 | 353062 |
| 115 x 10000 | 240 | 1 | 349058 |
| 115 x 10000 | 400 | 1 | 353060 |

**Klingspor Schleifsysteme GmbH und Co. KG**
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de